



whittle
W A X E S

For beautiful timber, naturally

WHITTLE WAXES EVOLUTION OBJECT OIL INFORMATION SHEET

Product Description: Whittle Waxes Evolution Object Oil

Maintenance oil for existing interior waxed surfaces.

- Use **Object Oil** to refresh surfaces treated with Evolution Classic, Satin and Gloss Hardwax Oil.
- Use **Matte Object Oil** to refresh surfaces treated with Evolution Matte Hardwax Oil.
- **Colours:** Object Oil is clear or can be pigmented in a range of colours, suitable for both domestic and commercial applications.
- **Replenishment:** Object Oil is used as a maintenance coat for surfaces already coated with Hardwax Oil. It removes most stains and minor scratching by buffing on a thin coat. For commercial areas the coat can be applied with a buffing machine at night and dry for morning with no aggressive odours.
- **Repair** for smaller areas such as kitchen and bathroom benchtops: Object Oil can be easily buffed on with a lint free cloth.
- **Safe** for humans, animals and plants after drying. Food and toy safe. Contains no biocidal substances or preservatives.

Recommended Tools:

- Stirring stick
- White buffing pad
Ø 400 mm
- Brush
- Lint free cloth
- Maroon pad

Clean tools:

with *Whittle Waxes Special Thinner*.

Coverage rate on a previously treated surface: Approximately 100 ml/m² per coat depending on timber species.

Coats needed: Single coat system for maintenance

Sheen Levels: classic and matte

Container sizes: 100ml, 500ml, 750ml, 2.5L

Storage: Cool but frost-free. 5 year shelf-life in unopened containers.

Drying time for maintenance coat:

Fast drying, 6-8 hours depending on temperature and airflow.

DO NOT GET WET DURING THIS TIME

Note: When using several containers with different lot numbers, they should be mixed together in a large container.

Maintenance of existing surface:

1. Vacuum the floor thoroughly.
2. Pour a small puddle on the floor no bigger than the palm of your hand.
3. Place the white pad on the buffing machine directly on the puddle.
4. Spread with a slow-speed rotary polisher and white pad (see video on website).
5. Buff the area until there is no evidence of swirl marks.
6. With a lint free cloth buff by hand around the floor's perimeter.

Care:

Maintenance: Sweep, wipe with a damp mop or vacuum. Occasionally wash with *Whittle Waxes Floor Care*. If necessary, re-oil.

Renovation: For intensive cleaning of heavily used or damaged areas: Clean with *Whittle Waxes Preparation Cleaner*, rinse well and when completely dry re-apply the Object Oil. No sanding required. In the case of pigmented areas there may be slight color variations (color change of the pigments by UV radiation).

Helpful Advice:

- **Colours:** For stains such as Treatex Colour Tones and Whittle Waxes Raw and Natural Stains, colours should be applied **before** the application of Object Oil. It is also possible to add pigment paste into the coat of Object Oil, but do not exceed 10%. In this case, buffing it on will give a more uniform result.
- **Anti-Slip:** In the case of stairs, *Whittle Waxes Anti-Slip* should be applied **between** coats.
- **Wood Filler** save the sanding dust from your last clean sanding of the floor to mix in with *REDifill Wood Filler*. Wood filler should be applied **before** application of Object Oil.

Ingredients: Refined natural oils based on soy, sunflower and colza oil, isoaliphates, lead-and bariumfree.



Important GHS notes: Follow the care instructions for oiled floors. EUH208: Contains Cobalt bis (2-ethylhexanoate). May produce an allergic reaction. In case of skin contact, we recommend wearing suitable gloves (nitrile). EUH210: Safety data sheet available on request. P101: If medical advice is needed, keep packaging or label handy. P102: Keep out of the reach of children. P103: Read label before use. When using several containers with different batch numbers, mix them together in a larger container. Only completely emptied containers may be recycled. Dried residue can be disposed of as household waste or as construction waste. Dispose of liquid residues at a collection point for old paint. ASN No.: 080112. EU threshold value for the product (A/f): 700 g/l (2007) / 700 g/l (2010). This product contains a maximum of 600 g/l VOC.

Disclaimer: Our technical advice in written form is given in good faith and on the basis of experiments, but it is only non-binding advice and does not release you from the obligation to test the products supplied by us as to their suitability for the particular purpose. Application, use and processing of the products outside our direct control are entirely your responsibility. Naturally we guarantee consistent quality of our products corresponding to the original sample. With release of new product information the previous information loses validity.