



# **POLYPRO**

## **PRODUCT DATA SHEET**

Gloss Timber and Cork Finish

### **Description**

For protecting and beautifying interior timber and cork floors. Handley Polypro is a competitively priced professional one can polyurethane which cures by absorbing moisture of the atmosphere to form a tough resilient coating which has excellent abrasion and chemical resistance.

### **PolyPro Features**

- ❖ One can – no mixing required
- ❖ Hard wearing, scratch resistant
- ❖ Flexible coating
- ❖ Heat and chemical resistant
- ❖ Resilient, last for years
- ❖ Excellent coverage
- ❖ Non slip surface
- ❖ Low maintenance
- ❖ Can be applied with a brush, roller or applicator

### **Coverage**

6-8 sqm per litre (approximately)

### **Caring for your Polypro Floor**

As complete curing of a Polypro floor takes a full seven days, care must be exercised during this time. Avoid dragging furniture etc over the surface. Use protective mats in traffic areas. To extend the life of the floor, mats should be used in doorways in order to remove dirt and grit from feet. Protective pads should be used on the legs of furniture. The floor should be swept frequently and washed with three litres of hot water and quarter cup of methylated sprits.

### **Application**

Please refer to directions on the can label. Handley Industries recommend a minimum of three coats applied liberally with either a brush roller or applicator. Clean equipment immediately after use with Handley Brush Cleaner.

### **Recoating**

As long as the coating is not worn through it is possible to recoat without a complete re-sand back to bare wood. The floor must be free of all traces of grease or wax. If there is any suspicion of grease or wax, use a degreaser and/or wax stripper prior to the application of Handley Industries Reglaze Solvent system.

### **Blockout and Staining**

A recent innovation has been the development of staining and blockout coloured floors. Such coatings are a fashionable yet economic alternative to other floor coverings. To avoid colour distortion after exposure to UV, light colours should be coated with one of the Handley aliphatic or non-yellowing products. The blockout and darker colours however can be used in conjunction with Handley Urethane Gloss, Satin or Lo-sheen finishes. Handley Polypro can be applied over a range of approved spirit stains. Contact us for our staining system.



**Caution**

This product may be harmful by inhalation. DO NOT breathe vapour. Avoid contact with skin and eyes. We recommend that you use a respirator when regularly applying this product. Safety equipment is available from Handley Industries Limited. When applying the initial coats, ensure there is good ventilation by opening all windows and doors. This is not recommended for final coats because it increases the risk of contamination by atmospheric dust.

**DO NOT use floor polish or other maintenance dressings.**