



URETHANE MATT

PRODUCT DATA SHEET

Timber and Cork Finish

Description

For protecting and beautifying interior timber and cork floors. Handley Urethane is a one can polyurethane which cures by absorbing moisture out of the atmosphere to form a tough resilient coating which has excellent abrasion and chemical resistance.

Urethane Features

- ❖ One can – no mixing required
- ❖ Flexible coating
- ❖ Resilient – lasts for years
- ❖ Non slip surface
- ❖ Can be applied with a brush or roller
- ❖ Hard wearing – scratch resistant
- ❖ Heat and chemical resistant
- ❖ Available in Gloss, Satin, Lo-Sheen or Matt
- ❖ Excellent coverage
- ❖ Low maintenance

Coverage

Approximately 8-10m²/litre

Caring for your Urethane Floor

As complete curing of a Urethane floor takes a full seven days, care must be exercised during this time. Avoid dragging furniture etc over the surface. Use protective mats in traffic areas. To extend the life of the floor, mats should be used in doorways in order to remove dirt and grit from feet. Protective pads should be used on the legs of furniture. The floor should be swept frequently and washed with three litres of hot water and quarter cup of Methylated Spirits.

Application

Please refer to directions on the can label. Handley Industries recommend a minimum of three coats applied liberally with either a brush or roller. Clean equipment immediately after use with Handley Brush Cleaner.

Colour Washing, Tinting and Staining

A recent innovation has been the development of colour washed and blackout coloured floors. Such coatings are a fashionable, yet economic alternative to other floor coverings. To avoid colour distortion after exposure to UV, light colours should be coated with one of the Handley aliphatic or non-yellowing products. The blackout and darker colours however can be used in conjunction with Handley Urethane Gloss, Satin, Lo-Sheen or Matt finishes. Handley Urethane can be applied over a range of approved spirit stains.

Re-Coating

As long as the coating is not worn through it is possible to re-coat without a complete re-sand back to bare wood. The floor must be free of all traces of grease or wax. If there is any suspicion of grease or wax, use a degreaser and/or wax stripper prior to application of Handley Industries Reglaze Solvent system.



Caution

This product may be harmful by inhalation. Do not breathe vapour. Avoid contact with skin and eyes. We recommend that you use a respirator when regularly applying this product. Safety equipment is available from Handley Industries Limited. When applying the initial coats, ensure there is good ventilation by opening all windows and doors. This is not recommended for final coats because it increases the risk of contamination by atmospheric dust.

DO NOT use floor polish or other maintenance dressings.